

Wisp 3/4" Thermostatic Valve Trim with Lever Handles

US-WP1000R

FEATURES

- Thermostatic valve trim with lever handles
- Single integrated volume control for 1 water outlet
- Vernet thermostatic cartridge and Fluhs flow control cartridge
- Cartridge restricts water supply should the hot or cold supply fail, to prevent scalding or thermal shock
- Integral shut-off non-return valves with filters to prevent cross flow

- Built-in service stops
- Available finishes:
 - US-WP1000RC Polished chrome
 - US-WP1000RN Polished nickel
 - US-WP1000RV Stainless
- Required rough (sold separately):
 - US-WLBP1000R




1 function

SPECIFICATION

- Flow rate: 12 gpm at 60 psi
- Water pressure maximum: Operating pressure of 60psi and static pressure of 144 psi
- Water pressure minimum: 20 psi
- Inlet connection: 3/4" NPT
- Outlet connection: 3/4" NPT
- Rough-in depth minimum: 3"
- Rough-in depth maximum: 4"

- Handle style: Lever
- Extension kit:
 - US-EK10125C Polished chrome
 - US-EK10125N Polished nickel
 - US-EK10125V Stainless
- Material: Brass
- Warranty: Limited lifetime Commercial: 1 year



LEVERS A: Water Control B: Temperature

CERTIFICATIONS

- Meets or exceeds ASME A112.18.1 / IAPMO Z124 / CSA B125.1
- Certifications: IAPMO(cUPC), State of Massachusetts, and others
- Code compliance: ADA, UPC, cUPC
- ADA compliant





