
WATERWORKS

INSTALLATION GUIDELINES


IMPORTANT:

- > To ensure this product is installed properly, you must read and follow these guidelines.
- > The owner/user of this product must keep this information for future reference.
- > This product must be installed by a professional licensed contractor.
- > Inspect this product to ensure you have all the parts required for proper installation.
- DRYWALL ANCHORS for a typical drywall installation are provided. Do NOT use the ANCHORS if mounting directly onto wood blocking or a stud.
- If further assistance is required, please contact Product Support at 1-800-927-2120 Monday through Friday, 8am - 6pm EST.
- > Refer to the separate Service Parts Documents for available replacement parts.




3. Dry-fit the SHELF to the finished wall and mark the ideal location making sure to hold the SHELF level.

NOTE: Verify the 15" [381mm] on-center spread.





Loosen, but do **NOT** remove, the SET SCREW on the bottom of each SHELF BRACKET to remove the MOUNTING PLATES then unthread and remove the RETAINING CAPS.

NOTE: Do NOT discard the O-RINGS provided.




 Using the previous marks as a reference, install the MOUNTING PLATES using the ANCHORS, if necessary, and SCREWS provided.





Using the O-RINGS provided, thread the BRACKETS into the CAPS. Adjust the orientation and securely tighten the BRACKETS into position.

NOTE: It **may be** necessary to repeat this step in order to tighten and align the BRACKETS properly.



Slide the ESCUTCHEONS and BRACKETS onto the MOUNTING PLATES then thread and securely tighten the SET SCREWS.