WATERWORKS

HENRY HNLS32

Henry Gooseneck Three Hole Deck Mounted Lavatory Faucet with Portoro Cylinders and Metal Lever Handles



SHOWN IN HENRY GOOSENECK THREE HOLE DECK MOUNTED LAVATORY FAUCET WITH PORTORO CYLINDERS AND METAL

INSPIRATION

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

TECHNICAL DETAILS

Adjustable versus Fixed Spray: Fixed Spray
Deck Thickness Maximum: 1 5/8"
Deck Thickness Minimum: 3/16"
Drain Depth Maximum: 2 5/8"
Drain Hole Diameter: 1 3/4"
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 1 1/4"
Flow Restriction Options: 1.0, 1.2, 1.5, 1.75, 2.2
Handle Spread Maximum: 12"
Handle Spread Minimum: 8"

Handle Spread Maximum: 12 Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn Depth / Width: 7 13/16" Drain Depth Minimum: 3/8" Height: 9"

Inlet Connection Size: 1/2"
Inlet Connection Type: Male with Supply Nut
Inlet Supply Spread Maximum: 12"
Inlet Supply Spread Minimum: 8"
Installation Type: Deck Mounted
Integrated Diverter: N
Integrated Spray: N
Number of Handles: Two

Number of Handles: Two
Number of Handles: Two
Number of Holes: Three Hole
Primary Material: Brass
Spout Swivel: N
Spray Included in Unit: N
Suggested Application: Bath
Valve Material: Ceramic
Water Pressure Maximum: 85.0 psi
Water Pressure Minimum: 20.0 psi
Water Pressure Recommended: 45.0 psi

CODES & STANDARDS

Code # HNLS32X: Complies with ASME A112.18.1/CSA B125.1, ASME A112.18.2 / CSA B125.2, NSF, CEC 61, ADA and 0.25% Weighted Average Lead Content. Certified with IAPMO, cUPC, NSF, CEC and State of MA.

PRODUCT FEATURES

Portoro is a marble from Italy and available in a polished finish.

 $The \ manufacturing \ process \ encompasses \ casting, \ turning, forging, hand-fitting \ and \ hand \ polishing.$

Portoro features elegant veining in shades of grey and gold that is a natural material so some variances will occur, making each piece unique.

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires 1.2gpm(4.5 L/min). Also available in other flow options. Contact a sales associate for details.

CERTIFICATIONS



HENRY HNLS32

Henry Gooseneck Three Hole Deck Mounted Lavatory Faucet with Portoro Cylinders and Metal Lever Handles

