WATERWORKS

RWLS30 R.W. ATLAS

R.W. Atlas Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Lever Handles



SHOWN IN R.W. ATLAS LOW PROFILE THREE HOLE DECK MOUNTED LAVATORY FAUCET WITH METAL LEVER HANDLES

INSPIRATION

Powerful shapes, genuine materials and unique aesthetic details. The original, impeccable vision of R.W. Atlas pairs American ingenuity with European craftsmanship.

TECHNICAL DETAILS

ADA Compliance: Yes

Adjustable versus Fixed Spray: Fixed Spray

Deck Thickness Maximum: 1 9/16" Deck Thickness Minimum: 3/8"

Drain Depth Maximum: 25/8" Drain Hole Diameter: 1 3/4"

Escutcheon Primary Material: Brass

Fittings Hole Diameter: 1 1/4" Handle Spread Maximum: 12"

Handle Spread Minimum: 8"

Handle Turn Angle: Quarter Turn

Depth / Width: 7 3/4"

Drain Depth Minimum: 3/8" Height: 4 3/8"

Inlet Connection Size: 1/2"

Inlet Connection Type: Male with Supply Nut

Inlet Supply Spread Maximum: 12"

Inlet Supply Spread Minimum: 8"

Installation Type: Deck Mounted

Integrated Diverter: N Integrated Spray: N

Length: 14 1/4"

Number of Handles: Two

Number of Holes: Three Hole

Primary Material: Brass

Restricted Maximum Flow Rate: 1.2 gpm

Spout Swivel: N

Spray Included in Unit: N

Suggested Application: Bath Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi

Water Pressure Minimum: 20.0 psi

Water Pressure Recommended: 45.0 psi

CODES & STANDARDS

Code # RWLS30: Complies with ASME A112.18.1/CSA B125.1, ASME A112.18.2 / CSA B125.2, NSF 61, NSF 372, CEC, ADA and 0.25% Weighted Average Lead Content. Certified with IAPMO, cUPC, NSF, CEC, DOE, State of MA and WRAS.

PRODUCT FEATURES

Features tumbled barrels marked with an engraved H and C. Includes European push touch style drain.

Meets or exceeds the Weighted Average Lead Requirements of 0.25%.

Available in 1.2gpm (4.5L/min)

CERTIFICATIONS







R.W. ATLAS RWLS30

R.W. Atlas Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Lever Handles

