WATERWORKS

R.W. ATLAS RWHS10

R.W. Atlas Handshower On Bar with Metal Handle



TECHNICAL DETAILS

ADA Compliance: Yes
Adjustable versus Fixed Spray: Fixed Spray
Diameter of Head: 2 11/16"
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 1"
Flow Restriction Options: 2.5, 2.2, 2.0, 1.75, 1.5, 0.92
Handshower / Spray Hose Length: 59"
Depth / Width: 6 1/8"
Height: 24 3/4"
Inlet Connection Size: 3/4"
Inlet Connection Type: Copper Compression
Installation Type: Wall Mounted
Integrated Diverter: N
Length: 3 1/2"

Pivot: Y Primary Material: Brass Suggested Application: Bath Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN R.W. ATLAS HANDSHOWER ON BAR WITH METAL HANDLE RWHS10

INSPIRATION

Powerful shapes, genuine materials and unique aesthetic details. The original, impeccable vision of R.W. Atlas pairs American ingenuity with European craftsmanship.

CODES & STANDARDS

Code # RWHS10: Complies with ASME A112.18.1/CSA B125.1, ADA, CEC and 0.25% Weighted Average Lead Content. Certified with IAPMO, cUPC, CEC, State of MA and WRAS.

PRODUCT FEATURES

Meets ADA requirements.

Adjustable handshower.

Stocked in 2.5gpm (9.5 L/min) and 1.75gpm (6.6 L/min). State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details.









R.W. ATLAS RWHS10

R.W. Atlas Handshower On Bar with Metal Handle

