

## R.W. ATLAS

RWXS01

R.W. Atlas Exposed Thermostatic Valve with Metal Wheel Handle



SHOWN IN R.W. ATLAS EXPOSED THERMOSTATIC VALVE WITH METAL WHEEL HANDLE| RWXS01

### TECHNICAL DETAILS

ADA Compliance: Yes  
 Adjustable versus Fixed Spray: Fixed Spray  
 Diameter of Head: 8 9/16"  
 Escutcheon Primary Material: Brass  
 Fittings Hole Diameter: 1"  
 Handshower / Spray Hose Length: 59"  
 Depth / Width: 7 1/8"  
 Height: 9 13/16"  
 Inlet Connection Size: 3/4"  
 Inlet Connection Type: Copper Compression  
 Inlet Supply Spread Maximum: 11 3/4"  
 Inlet Supply Spread Minimum: 11 1/2"  
 Installation Type: Wall Mounted  
 Integrated Diverter: N  
 Length: 13 13/16"  
 Number of Handles: One  
 Pivot: N  
 Primary Material: Brass  
 Restricted Maximum Flow Rate: 2.5 gpm  
 Spray Included in Unit: N  
 Suggested Application: Bath  
 Valve Material: Bi-metal Strip  
 Water Pressure Maximum: 85.0 psi  
 Water Pressure Minimum: 20.0 psi  
 Water Pressure Recommended: 45.0 psi

### INSPIRATION

Powerful shapes, genuine materials and unique aesthetic details. The original, impeccable vision of R.W. Atlas pairs American ingenuity with European craftsmanship.

### CODES & STANDARDS

Code # RWXS01: Certified with IAPMO & State of MA. Complies with ASME A112.18.1/CSA B125.1, ANSI 117.1 ADA & ASTM E 1621-05.

### PRODUCT FEATURES

Features knurled detail on the handle.  
 Maintains concealed piping for shower head and handshower options.  
 Offers a temperature limit stop with override button.  
 Special Order lead time is 10 - 12 weeks.



### PRODUCT (NOTES)

Includes 3/4" Thermostatic Valve and requires a separate volume control valve and trim to operate.

# WATERWORKS

## R.W. ATLAS

RWXS01

R.W. Atlas Exposed Thermostatic Valve with Metal Wheel Handle

