EASTON

EAXS34

Easton Classic Exposed Thermostatic System with 8" Shower Rose with Black Porcelain Lever Handle



SHOWN IN EASTON CLASSIC EXPOSED THERMOSTATIC SYSTEM WITH 8" SHOWER ROSE WITH BLACK PORCELAIN LEVER

INSPIRATION

Drawing on Edwardian style, Easton is the most extensive Waterworks family; a range of moods and a selection of products from fittings to furniture.

TECHNICAL DETAILS

ADA Compliance: Yes Adjustable versus Fixed Spray: Fixed Spray Diameter of Head: 8" Fittings Hole Diameter: 1 3/8" Flow Restriction Options: 2.5, 2.0, 1.75, 1.5, 0.92 Handshower / Spray Hose Length: 59" Index Color / Finish and Material: Metal Inlet Connection Size: 3/4" Inlet Connection Type: Copper Compression Inlet Supply Spread Maximum: 8 3/16" Inlet Supply Spread Minimum: 8 1/16" Installation Type: Wall Mounted Integrated Diverter: N Primary Material: Brass Suggested Application: Bath Valve Material: Brass Water Pressure Maximum: 75.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

CODES & STANDARDS

Code # EAXS34X: Certified with cUPC, NSF, IAPMO, CSA

PRODUCT FEATURES

Built in Anti-scald protection.

Optional handle materials include porcelain and semi-precious stones.

The pillowed propeller on the cross handle makes the product fit comfortably in the hand.

Add a handshower to this exposed system. Handshower not included.

Stocked in 2.5gpm (9.5 L/min) and 1.75gpm (6.6 L/min). State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate

CERTIFICATIONS



PRODUCT (NOTES)

Valve Included, Handshower Sold Separately

EASTON

EAXS34

Easton Classic Exposed Thermostatic System with 8" Shower Rose with Black Porcelain Lever Handle

