WATERWORKS

R.W. ATLAS

RWXT40

R.W. Atlas Exposed Deck Mounted Tub Filler with Handshower and Wheel Handles



L SHOWN IN R.W. ATLAS EXPOSED DECK MOUNTED TUB FILLER WITH HANDSHOWER AND WHEEL HANDLES| RWXT40

INSPIRATION

Powerful shapes, genuine materials and unique aesthetic details. The original, impeccable vision of R.W. Atlas pairs American ingenuity with European craftsmanship.

TECHNICAL DETAILS

Adjustable versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 2 13/16" Deck Thickness Minimum: 0" Diameter of Head: 1 7/8" Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 1/8" Flow Restriction Options: 2.5, 2.0, 1.75, 1.5, 0.92 Handle Spread Maximum: 8" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn Depth / Width: 11 11/16" Height: 12 1/8" Inlet Connection Size: 3/4" Inlet Connection Type: Male NPT Inlet Supply Spread Maximum: 8" Inlet Supply Spread Minimum: 8" Installation Type: Deck Mounted Integrated Diverter: N Integrated Spray: N Length: 13 1/2" Number of Handles: Two Primary Material: Brass Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi



Includes Deck Unions

A handshower adds a degree of comfort, making it easy to rinse the bath or even a pet. Unrestricted (spout) water flow of approximately 12 gpm (45 L/min).

Stocked in 2.5gpm (9.5 L/min) and 1.75gpm (6.6 L/min) for handshower. State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details.





R.W. ATLAS

RWXT40

R.W. Atlas Exposed Deck Mounted Tub Filler with Handshower and Wheel Handles

