DASH

DSLS30

Dash Gooseneck Three Hole Deck Mounted Lavatory Faucet with Metal Lever Handles



TECHNICAL DETAILS

Deck Thickness Maximum: 1 9/16" Deck Thickness Minimum: 1/4" Drain Assembly Materials: Brass, Rubber, Plastic Drain Depth Maximum: 2 5/8" Drain Hole Diameter: 1 3/4" Drain Style: Push-Touch Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 3/8" Flow Restriction Options: 1.75, 1.5, 1.2, 1.0 Handle Spread Maximum: 12" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn Depth / Width: 7 15/16" Drain Depth Minimum: 3/8" Height: 7 15/16" Inlet Connection Size: 1/2" Inlet Connection Type: Male with Supply Nut Inlet Supply Spread Maximum: 12" Inlet Supply Spread Minimum: 8" Installation Type: Deck Mounted Length: 16 1/16" Number of Handles: Two Number of Holes: Three Hole Primary Material: Brass Restricted Maximum Flow Rate: 2.2 gpm Spout Swivel: N . Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

L SHOWN IN DASH GOOSENECK THREE HOLE DECK MOUNTED LAVATORY FAUCET WITH METAL LEVER HANDLES| DSLS30

INSPIRATION

A blend of art and function, Dash pays homage to design elements of the 1930s with pared-down shapes, softened curves and minimal details.

PRODUCT FEATURES

Metal Lever Handle Includes European push touch style drain. Stocked in Nickel, Chrome, Unlacquered Brass, and Matte Nickel finishes Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires 1.2gpm(4.5 L/min). Also available in other flow options. Contact a sales associate for details.





DASH

DSLS30

Dash Gooseneck Three Hole Deck Mounted Lavatory Faucet with Metal Lever Handles

