DASH DSLS60

Dash Three Hole Wall Mounted Lavatory Faucet with Metal Cross Handles



L Shown in dash three hole wall mounted lavatory faucet with metal cross handles| DSLS60

## **INSPIRATION**

A blend of art and function, Dash pays homage to design elements of the 1930s with pared-down shapes, softened curves and minimal details.

## PRODUCT FEATURES

Metal Cross Handle

Includes European push touch style drain.

Stocked in Nickel, Chrome, Unlacquered Brass, and Matte Nickel finishes

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires 1.2gpm(4.5 L/min). Also available in other flow options. Contact a sales associate for details.

## **TECHNICAL DETAILS**

Control Valve Rough-in Depth Maximum: 5 1/2" Control Valve Rough-in Depth Minimum: 3" Drain Assembly Materials: Brass, Rubber, Plastic Drain Depth Maximum: 25/8" Drain Hole Diameter: 1 3/4" Drain Style: Push-Touch Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 3/8" Flow Restriction Options: 1.75, 1.5, 1.2, 1.0 Handle Spread Maximum: 8" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn Depth / Width: 7 13/16" Drain Depth Minimum: 3/8" Height: 2 7/8" Inlet Connection Size: 1/2" Inlet Connection Type: Male NPT Inlet Supply Spread Maximum: 8"

Inlet Supply Spread Maximum: 8"
Inlet Supply Spread Minimum: 8"
Installation Type: Wall Mounted
Length: 10 15/16"
Number of Handles: Two
Number of Holes: Three Hole
Primary Material: Brass
Restricted Maximum Flow Rate: 2.2 gpm
Spout Swivel: N
Suggested Application: Bath

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

## PRODUCT (NOTES)

Product Requires Universal Lavatory Wall Mounted Rough Valve [GULV27]. Valve Sold Separately.

DASH DSLS60

Dash Three Hole Wall Mounted Lavatory Faucet with Metal Cross Handles

