BOND BLS72E

Bond Union Series Wall Mounted Lavatory Faucet with Guilloche Pinstripe Lever Handles



TECHNICAL DETAILS

ADA Compliance: Yes Drain Depth Maximum: 2 5/8" Drain Depth Minimum: 3/8" Drain Hole Diameter: 1 3/4" Drain Style: Push Touch Fittings Hole Diameter: 1 3/8" Handle Spread Maximum: 8" Handle Spread Minimum: 8"

Handle Turn Angle: Quarter Turn Each Way Inlet Connection Size: 1/2"

Inlet Connection Size: 1/2"
Inlet Connection Type: Female NPT
Number Of Holes: Three Hole
Primary Material: Brass

Restricted Maximum Flow Rate: 1.2 gpm

Spout Swivel: N

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN BOND UNION SERIES WALL MOUNTED LAVATORY FAUCET WITH GUILLOCHE PINSTRIPE LEVER HANDLES | BLS72E

INSPIRATION CODES & STANDARDS

Modern designs infused with rare soul and artistry. Explore our wide range of Bond bath and kitchen elements, from fittings to fixtures to hardware.

PRODUCT FEATURES

Lever Handles

Includes Universal Push-Touch Drain (UNLD23) which fits 1-1/2" through 1-3/4" drain hole openings

Stocked in Nickel and Brass

Available in 1.2gpm (4.5L/min) flow rate; Requires valve, sold separately: GULV25 (USA) or GU25LV (UK/International)

CERTIFICATIONS

PRODUCT (NOTES)

BOND BLS72E

Bond Union Series Wall Mounted Lavatory Faucet with Guilloche Pinstripe Lever Handles

