UNIVERSAL USH305

Universal Transitional 5" Showerhead with Adjustable Spray



### **TECHNICAL DETAILS**

Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

Adjustable Versus Fixed Spray: Adjustable Spray Inlet Connection Size: 1/2" Inlet Connection Type: Female Straight Threads with Rubber Washer Pivot: Y Primary Material: Brass Restricted Maximum Flow Rate: 1.75 gpm Water Pressure Maximum: 85.0 psi

SHOWN IN UNIVERSAL TRANSITIONAL 5" SHOWERHEAD WITH ADJUSTABLE SPRAY | USH305

## INSPIRATION

Our Universal collection features timeless designs complementing any of our Waterworks. With a wide range of product, from fittings to accessories, Universal adds exquisite proportion and balance to any environment.

#### **CODES & STANDARDS**

#### **PRODUCT FEATURES**

Made of Brass

Swiveling 8" rain showerhead

Easy clean rubber nozzles prevent calcium buildup

Stocked in Brass, Chrome and Nickel

Rain showerhead available in 1.75gpm (6.6L/min) flow rate

## **CERTIFICATIONS**

# PRODUCT (NOTES)

UNIVERSAL USH305

Universal Transitional 5" Showerhead with Adjustable Spray

